



## Section 1 - Product and Company Identification

<b>Material Name</b>	- <b>Grey Phenolic Rust Inhibitive Primer</b>
<b>Chemical Category</b>	- Paint
<b>Product Code</b>	- DYC-MP75
<b>Product Description</b>	- Primer.
<b>Product Use</b>	- Primes surface to retard corrosion..
<b>Synonyms</b>	- Primer
<b>Manufacturer</b>	- Dyco Paints Inc. 5850 Ulmerton Rd. Clearwater, FL 33760 United States www.suncoatings.com Please use "Contact Us" form on the website
<b>Telephone</b>	813-367-4444
<b>Technical</b>	- 813-248-2101 - Customer Service: 8 AM - 5 PM M-F Eastern Standard Time
<b><u>Emergency</u></b>	- 800-424-9300 - CHEMTREC
<b><u>Emergency</u></b>	- 703-527-3887 - CHEMTREC (Outside US)
<b>Last Revision Date</b>	- 7-17-2015

## Section 2 - Hazards Identification

### GHS HAZARDS AND PRECAUTIONS

#### SIGNAL WORD: WARNING!

*Flammable liquid (paste) and Vapor. Contains Combustible Petroleum Distillates. Harmful or Fatal if swallowed. Keep away from heat, sparks, and open flame. Avoid prolonged breathing of vapor and use only in adequate ventilation. Repeated and prolonged overexposure to solvent vapor may cause brain and nervous system damage, respiratory tract irritation, dizziness, or loss of consciousness. May cause skin and eye irritation.*

<b>Prevention</b>	Avoid breathing dust, fume, gas, mist, vapors and/or spray. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces. - No smoking. Use personal protective equipment as required. Keep out of reach of children.
<b>Response</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
<b>Storage/Disposal</b>	Store in a closed container. Store in a well-ventilated place. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



<b>Physical Form</b>	- Liquid
<b>Color</b>	- White
<b>Odor</b>	- Petroleum solvent odor.
<b>Flash Point</b>	- <b>81 F(27.2 C)</b>
<b>OSHA HCS 2012</b>	- Flammable Liquids - Category 3, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2A

**WHMIS**

- Class B - Flammable and Combustible Materials - Division 3, Class D - Poisonous and Infectious Materials - Division 2 - Subdivision A

**GHS**

- R65, R25, R36/37/38, R45
- Flammable Liquids - Category 3, Skin Corrosion/Irritation - Category 2, Serious Eye Damage, Eye Irritation - Category 2A

**Route Of Entry**

- Inhalation, Skin, Eye, Ingestion/Oral

**Potential Health Effects****Inhalation****Acute (Immediate)**

- May cause irritation. Excessive breathing of high vapor concentration can cause possible unconsciousness and even asphyxiation.

**Chronic (Delayed)**

- Refer to other information found in Section 11-Toxicology.

**Skin****Acute (Immediate)**

- May cause irritation.

**Chronic (Delayed)**

- Repeated and prolonged exposure to the skin may cause dermatitis.

**Eye****Acute (Immediate)**

- May cause irritation.

**Chronic (Delayed)**

- Repeated and prolonged exposure may cause irritation.

**Ingestion****Acute (Immediate)**

- May be harmful or fatal if swallowed.

**Chronic (Delayed)**

- Repeated and prolonged exposure may be harmful.

**Carcinogenic Effects**

- This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 - Toxicological Information for more details.

Carcinogenic Effects			
	CAS	IARC	NTP

**Section 3 - Composition/Information on Ingredients**

Chemical Name	CAS	%(wt)	LD50/LC50	EU R & S Phrases	Other
Alkyd Resin	Proprietary	20.0%	NDA	NDA	NDA
Xylene	1330-20-7	<17.0%	Acute oral toxicity (LD50): 2119 mg/kg [Mouse]. Acute dermal toxicity (LD50): >1700 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50):5000 4 hours [Rat].		NDA
Barium Sulfate	7727-43-7	13.0%	NDA	NDA	NDA
Talc	14807-96-6	12.0%	NDA	NDA	NDA
Zinc Phosphate	7779-90-0	< 3.0%	Ingestion/Oral-Rat LD50 · 5000 mg/kg		NDA

**This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.**

See Section 11 for Toxicological Information.

## Section 4 - First Aid Measures

- Inhalation** - IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. Move victim to fresh air. If breathing is difficult, give oxygen.
- Skin** - IF ON SKIN: Wash with plenty of soap and water. If irritation develops and persists, get medical attention.
- Eye** - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Ingestion** - If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

## Section 5 - Fire Fighting Measures

- Extinguishing Media** - LARGE FIRE: Water spray, fog or regular foam.  
SMALL FIRES: Dry chemical, CO<sub>2</sub>, water spray or regular foam.
- Unsuitable Extinguishing Media** - Do not use direct stream of water.
- Firefighting Procedures** - Fight advanced or massive fires from safe distance or protected location. Avoid water in a straight hose stream as the stream will cause splatter and spread fire. If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and are ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
- Unusual Fire and Explosion Hazards** - Combustible liquid. May release irritating or toxic gases, fumes, or vapors.
- Hazardous Combustion Products** - Carbon monoxide, carbon dioxide, hydrocarbons.
- Protection of Firefighters** - Firefighters should wear self-contained breathing apparatus and full protective gear.
- Flash Point** - **81°F(27.2°C) CC (Closed Cup)**
- Explosion Limits**
- Upper** - 6 %
- Lower** - .9 %
- Autoignition Temperature** - 500 °F (260 C)

## Section 6 - Accidental Release Measures

- Personal Precautions** - Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stay upwind and Ventilate the area before entry.
- Emergency Procedures** - ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can without risk. Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. Keep unauthorized personnel away.
- Environmental Precautions** - Prevent entry into waterways, sewers, basements or confined areas.
- Containment/Clean-up Measures** - Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in suitable container. Do not use water to flush spill area. Use appropriate Personal Protective Equipment (PPE).
- Prohibited Materials** - Avoid contact with strong oxidizing agents.

## Section 7 - Handling and Storage

- Handling** - KEEP OUT OF THE REACH OF CHILDREN! Keep away from heat and ignition sources – No Smoking. Use only with adequate ventilation.

- Storage** - Store in a well-ventilated place. Keep container tightly closed. Keep container/package tightly closed in a cool, well-ventilated place. No open flames, no sparks and no smoking.
- Special Packaging Materials** - No data available
- Incompatible Materials or Ignition Sources** - Avoid contact with strong oxidizing agents and acids.

## Section 8 - Exposure Controls/Personal Protection

### Personal Protective Equipment Pictograms



- Respiratory** - In case of insufficient ventilation, wear suitable respiratory equipment. If listed exposure limits are expected to be exceeded, use approved respiratory protection suitable for the hazard.
- Eye/Face** - Wear ANSI approved safety glasses with side shields or safety goggles.
- Hands** - Wear chemical protective gloves made of Nitrile or Neoprene.
- Skin/Body** - Wear clothing that covers the skin to prevent skin exposure.
- General Industrial Hygiene Considerations** - Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling. Avoid breathing vapors.
- Engineering Measures/Controls** - Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

Exposure Limits/Guidelines					
	Result	ACGIH	Canada Ontario	OSHA	United States - California
Xylene (1330-20-7)	TWAs	100 mg/m <sup>3</sup> TWA	100 mg/m <sup>3</sup> TWAEV	150 mg/m <sup>3</sup> TWA	100 mg/m <sup>3</sup> PEL

Exposure Control Notations

ACGIH

#### Key to abbreviations

- PEL = Permissible Exposure Level determined by the Occupational Safety and Health Administration (OSHA)
- TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

## Section 9 - Physical and Chemical Properties

- Physical Form** - Liquid
- Appearance/Description** - Grey Paint

<b>Color:</b> Grey	<b>Odor:</b> Petroleum solvent odor.		
<b>Taste:</b> NDA	<b>Odor Threshold:</b> NDA		
<b>Boiling Point:</b>	300 to 400 F(148.8889 to 204.4444 C)	<b>Vapor Pressure:</b>	= 2 mmHg (torr) @ 68 F(20 C)
<b>Melting Point:</b>	NDA	<b>Vapor Density:</b>	= 1 Air=1
<b>Specific Gravity/Relative Density:</b>	= 1.56 Water=1	<b>Evaporation Rate:</b>	NDA
<b>Density:</b>	= 13.00 lbs/gal	<b>VOC (Wt.):</b>	= 3.49 lbs/gal
<b>Bulk Density:</b>	NDA	<b>VOC (Vol.):</b>	< 418 g/L
<b>pH:</b>	NDA	<b>Volatiles (Wt.):</b>	NDA
<b>Water Solubility:</b>	No	<b>Volatiles (Vol.):</b>	= 50.0 %
<b>Solvent Solubility:</b>	Yes	<b>Flash Point:</b>	81° F(27.2°C)
<b>Viscosity:</b>	90 KU	<b>Flash Point Test Type:</b>	CC (Closed Cup)

<b>Coefficient of Water:</b>	NDA	<b>Autoignition:</b>	500 F(260 C)
------------------------------	-----	----------------------	--------------

## Section 10 - Stability and Reactivity

<b>Stability</b>	- Stable under normal temperatures and pressures.
<b>Hazardous Polymerization</b>	- Hazardous polymerization will not occur.
<b>Conditions to Avoid</b>	- Avoid contact with strong oxidizing agents and flame.
<b>Incompatible Materials</b>	- Strong oxidizers and acids.
<b>Hazardous Decomposition Products</b>	- Carbon monoxide, carbon dioxide and hydrocarbons.

## Section 11 - Toxicological Information

Component Name	Concentration	CAS	Data
Xylene	<17.0%	1330-20-7	Acute oral toxicity (LD50): 2119 mg/kg [Mouse]. Acute dermal toxicity (LD50): >1700 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50):5000 4 hours [Rat].
Zinc Phosphate	<3.0%	7779-90-0	Ingestion/Oral-Rat LD50 · 5000 mg/kg

**Other Component Information** - IARC has concluded that none of the following chemicals in this product are carcinogenic to humans.

**Other Information** -

## Section 12 - Ecological Information

<b>Ecological Fate</b>	- No data available.
<b>Persistence/Degradability</b>	- No data available.
<b>Bioaccumulation Potential</b>	- No data available.
<b>Mobility in Soil</b>	- No data available.

## Section 13 - Disposal Considerations

**Product** - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transportation Information

**DOT – Department of Transportation** - UN1263 Pkg. Group 3 Hazard Class 3 Limited Quantity Exemption under 1.2 Gallons.

**TDG Transportation Other Information**▪: Not Restricted under General Exemption for small container packaging.

**TDG - Canada Transportation of Dangerous Goods:** UN1263; Hazard Class: 3; Packing Group: III 1.33 Class 3, Flammable Liquids

**IMO/IMDG –International Maritime Transport** ▪ IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages.

**IATA - International Air Transport Association** - UN1263; Hazard Class: 3; Packing Group: III.

## Section 15 - Regulatory Information

**SARA Hazard Classifications  
Risk & Safety Phrases**

- Acute, Chronic
- California PROP 65: Asphalt and Asphalt Fumes may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm. .

State Right To Know					
Component	CAS	MA	MN	NJ	PA
Alkyd Resin	Proprietary	No	No	No	No
Xylene	1330-20-7	Yes	Yes	Yes	Yes
Barium Sulfate	7727-43-7	No	No	No	No
Talc	14807-96-6	No	No	No	No
Zinc Phosphate	7779-90-0	No	No	No	No

Inventory			
Component	CAS	EU EINECS	TSCA
Alkyd Resin	Proprietary	No	No
Xylene	1330-20-7	Yes	Yes
Barium Sulfate	7727-43-7	Yes	Yes
Talc	14807-96-6	Yes	Yes
Zinc Phosphate	7779-90-0	Yes	Yes

**United States**

Environment

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

Alkyd Resin	Proprietary	Not Listed
Xylene	1330-20-7	Listed
Barium Sulfate	7727-43-7	Not Listed
Talc	14807-96-6	Not Listed
Zinc Phosphate	7779-90-0	Not Listed

**Section 16 - Other Information**

**Last Revision Date**

- 7/17/2015

**Prepared By**

- Israel Gutman

**Disclaimer/Statement of Liability**

- This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Dyco Paints Inc. does not accept liability for any loss or damage that may occur from the use of this information.

for

NFPA

