



FASTRIBE Traffic Marking Paint DOT Version 3260, 3270, 3280, 3285, 3290 Data Sheet

CAN BE USED ON:

- Concrete Surfaces
- Asphalt Surfaces
- Primed Metals
- Curbing
- Airfields
- Factory Floors
- Garage Floors and Sidewalks
- Concrete/Brick/Cinder Block

COLORS:

- 3260 White
- 3285 Red
- 3270 Yellow
- 3290 Black
- 3280 Blue

FASTRIBE is an ultra-premium fast-drying traffic marking paint that can be used on a variety of surfaces. Through the utilization of 100% Acrylic with Ambient Cure Cross Linking Technology, this product provides excellent adhesion and chemical resistance properties not seen in other marking paints. This product meets and or exceeds the requirements of Federal Specification TT-P-1952E and conforms to the guidelines of Master Painters Institute MPI #97.

READ AND FOLLOW ALL DIRECTIONS: All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Rusty metal must be cleaned with a wire brush and primed with a suitable primer before application of this product. Pressure washing entire surface is recommended for best results. Surfaces with mildew growth or stains must be cleaned with a bleach solution (2 parts water to one part bleach) prior to application. Be certain all surfaces are thoroughly rinsed and dry prior to applying coating.

PRECAUTION: Do not freeze. Wear protective clothing and eyewear during application of this product. Do not transport on passenger seats or inside passenger compartment of any vehicle. Store product in cargo area of vehicle, and secure with protective cloths to prevent accidental spill damage. Do not store at temperature above 100°F (37°C). Do not use in drinking water or food systems.

APPLICATION & COVERAGE RATE: Apply an even coat at approximately 13-15 wet mils, depending on the surface. May be applied by brush, roller, airless sprayer or striping machine. Dries to touch in 2-5 minutes, may be longer in cooler temperatures, higher humidity and thicker films. The coating may be subjected to traffic in 1 hour. If two coats are desired or necessary, this can be performed within 30 minutes of the initial coat.

DRY TIME: Dry-to-Touch – 10 minutes. Light Foot Traffic – 30 minutes, Vehicle Traffic-1-2 hours.

CLEAN-UP: Clean tools with soap and water.

PRECAUTIONS: DO NOT allow stored product to freeze. Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure the lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not store at temperatures above 100° F.

FOR BEST RESULTS:

DO NOT THIN - The addition of water will degrade the drying efficiency.

DO NOT APPLY – If heavy dew or rain is expected during application.

CAUTION: Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of warm water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent). Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention, immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Do not use in drinking water or food systems. Seal container when not in use.

NOTICE: Yearly inspection is highly recommended. This information is based on our best knowledge and experience. Since we have no control over application or conditions, our only obligation shall be to replace any material proved defective. We assume no liability for damage of any kind and the user accepts the product "as is". The suitability of the product for an intended use shall be solely up to the user.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Generic Type	100% Acrylic with Cross-Linking Technology
Weight Per Gallon	13.80lbs.
Solids by Weight	77.0%
Solids by Volume	63.0%
Gloss Reading at 60 °	1.0 - 6.0
Viscosity (ASTM D-2697)	80-90 KU
Film Dry Thickness	8.0 mil
Film Wet Thickness	13.0 mil
Consistency	Roller, Striping Machine
Suggested Coverage (varies per substrate)	390 ft./gal @ 4in. width 13.5Gal./Mile @ 4in. width
Type of Cure	Oxidative
Dry to Touch (50% Relative Humidity, 70°F)	2-3 Minutes
Foot Traffic (50% Relative Humidity, 70°F)	10-15 Minutes
Vehicle Traffic (50% Relative Humidity, 70°F)	45-60 Minutes
Clean-up Tools	Water
VOC	Less than 100g/l
APPROXIMATE SHIPPING WEIGHTS: Note - all weights include container.	
1 gallon (3.8L)	14lbs.
(4) 1 gallon containers/case	56lbs.
5 gallons (18.9L)	70lbs.
55 drums (208.2L)	770lbs.

FIRST AID: If swallowed, gently wipe or rinse the inside of the mouth with water. Water may be given if person is alert. Do NOT induce vomiting. Get medical attention immediately. If skin/eye contact occurs, flush the affected areas with warm water for at least 15 minutes. Remove contact lens. A mild soap may be used on skin if available. If inhaled, remove from area to fresh air. If breathing is difficult, get medical attention immediately. Take MSDS or label information.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION!

HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

CALIF. PROP. 65 • WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Use proper protection and adequate ventilation, when using product.

CHEMICAL COMPOSITION:

Prime Pigments	7.0%
Reinforcement Pigments	53.0%
Vehicle	40.0%

Product is asbestos free.

WARRANTY AND DISCLAIMER: For limited warranty and disclaimer information, contact the Sun Paints & Coatings corporate office at 1-800-247-9691.

