



DYC69XX

INSTACOURT

6960 - 6984 Data Sheet

CHARACTERISTICS

InstaCourt™ is an All-In-One Sport Surface Coating that provides a non-skid, durable, acrylic sports finish for concrete and asphalt surfaces. InstaCourt's tough, long-lasting surface can be used on driveways, outdoor courts, running tracks, playgrounds, and other recreational areas.

RECOMMENDED USES

- Driveways
- Outdoor Courts
- Running Tracks
- Playgrounds
- Outdoor Recreational Surfaces

FEATURES/BENEFITS

- Superior adhesion to bare concrete surfaces
- Uniform Opaque Low Sheen Finish
- Resists Fading, Cracking and Peeling
- Resists Mildew
- Self Priming
- Fast Drying

SPECIAL NOTES

Recommended for application on unpainted, untreated concrete that has cured for at least 30 days. As a maintenance coat it may be re-applied to itself annually after proper cleaning.

FOR ADDITIONAL INFORMATION

See SDS or call toll-free 1-800-282-7901.

TECHNICAL DATA

Vehicle Type Acrylic
 Gloss Reading at 60 ° <10
 Solids by Weight..... 40.0%
 Solids by Volume..... 30.0%
 Film Dry Thickness 2-3 Mills
 Viscosity (ASTM D-2697) ... 100 KU
 VOC (less exempt solvents) < 100 g/L.
 Weight per Gallon 9.85lbs.

COVERAGE

200 to 250 Sq.Ft./Gal.
(Actual coverage may vary depending on type of substrate and application method.)

AVAILABLE COLORS

6971 Purple	6972 Grey
6973 Orange	6974 Yellow
6975 Navy	6976 Blue
6977 Burgandy	6978 Light Blue
6979 Hunter Green	6980 Green
6981 Red	6982 Burnt Orange
6983 Black	6984 White

KEY ATTRIBUTES

Application Temperatures: 50 - 110 °F (10 - 43.33 °C)
 Application Tools: Brush, Roller or Spray
 Dry Times: Touch - 1 Hour; Recoat - 2 Hour
 (Dry Time Based on 77 °F (25 °C), 50% Relative Humidity)
 Thinner: Water
 Clean Up: Soap and Warm Water

PHYSICAL PROPERTIES

Mildew Resistance Excellent
 Flash Point..... 212 °F (100 °C)





DYC69XX

INSTACOURT

6960 - 6984 Precautions & Application Guide

FOR USE ON: Concrete and asphalt surfaces usually found in driveways, garages, walkways, and patios. Not recommended for wood.

PRECAUTION: Do not freeze. Wear protective clothing, gloves and eyewear during application and cleanup of this product. Do not transport on passenger seats or inside passenger compartment of any vehicle. Store product in cargo area of vehicle, and secure with protective cloths to prevent accidental spill damage. Do not store at temperature above 100 °F (37.77 °C). Do not use in drinking water or food systems.

READ AND FOLLOW ALL DIRECTIONS: Surfaces must be clean, dry and sound. Contaminants such as dirt, dust, grease, wax, oil, soap film, rust, mold, mildew, bond breakers and curing compounds must be removed before application. Loose, chipping and peeling of previous coating must be removed before application. Repair holes and cracks with an appropriate patching material. Clean surfaces with bleach solution [one (1) part bleach to four (4) parts water] and a stiff bristle brush. If mildew is present, treat with a mildew remover. Rinse with clean water and let dry one (1) to two (2) days before application. Do not apply to damp surfaces or when surface temperature is below 50 °F (10 °C) or above 100 °F (37 °C). Do not apply if rain is prevalent. Do not thin.

PREPARING NEW AND PREVIOUSLY COATED SURFACES: Allow new exterior concrete to cure a minimum of 30 days and a minimum of 45 days for new interior concrete before application. Pressure cleaning is recommended. Acid etching is not required. For best results on previously coated or bare non-porous slick concrete, prime the surface with DYCO 9040 TUFF GRIP.

TINTING: Tint with approved colorants. Factory-tinted colors cannot be re-tinted unless indicated on label as tintable. Please see the front panel of this package to determine the colors included in this kit.

APPLICATION NOTE: Depending on application and substrate conditions some colors such as Yellow or Orange may require two coats for full coverage.

APPLICATION: Directions for application included inside the original kit. Mix thoroughly before use. Two coats may be required to achieve proper color opacity. Apply first coat evenly with a medium nap roller, or brush. Do not leave puddles or roller marks. Coverage is 175-225 sq. ft./gal. depending on surface porosity and application method. Ready for recoat in four (4) hours. Dries to touch in two (2) hour @ 77 °F (25 °C) and 50% Relative Humidity. Ready for foot traffic in two (2) hours and vehicle traffic in 72 hours. Low temperature, high humidity, thick films or poor ventilation will increase these dry times. Application to concrete roof tiles is for decorative and protective purposes only.

This product is not designed to stop leaks in roofs.

TOOLS & APPLICATORS / CLEANING: Medium nap roller or brush. Cleans with soap and water.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.


CAUTION!

HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: If swallowed, gently wipe or rinse the inside of the mouth with water. Water may be given if person is alert. Do NOT induce vomiting. Get medical attention immediately. If skin/eye contact occurs, flush the affected areas with room temperature water for at least 15 minutes. Remove contact lens. A mild soap may be used on skin if available. If inhaled, remove from area to fresh air. If breathing is difficult, get medical attention immediately. Take SDS or label information.

VOC: The products contained in this kit have a maximum VOC of less than 100 g/L. Please see individual containers for actual VOC content.

VOC calculations based on manufactured tint base.



CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

WARRANTY AND DISCLAIMER: This product is in accordance with the specifications set forth herein. If the product proves to be defective within a 6-month period from the time of sale, the product shall be replaced at the cost of Sun Paints & Coatings. Such replacement is and shall be the only liability of Sun Paints & Coatings. Sun Paints & Coatings shall not be responsible to the consumer or any person for the labor cost of any kind or any other costs or damages associated with the product or its installation, application or reapplication or any damages resulting therefrom. This warranty is exclusive and there are no other warranties either expressed or implied including warranties of fitness or merchantability. No other written or oral representation by any person, entity, dealer, installer or representative of Sun Paints & Coatings shall have any force or effect.

Safety Data Sheet available upon request.



Sun Paints & Coatings / Dyco Paints • 5850 Ulmerton Road • Clearwater, FL 33760
Phone: 1.800.282.7901 • Facsimile: 727.536.0561 • www.SunPaintsAndCoatings.com

G-18
R-2