



3019-1-61

SILICONIZED ACRYLIC LATEX CAULK
Data Sheet

DYNAMITE 3000 WHITE

- Interior Caulk
- Easy Water Clean Up
- General Use

DYNAMITE 3000 is a **Siliconized Acrylic Latex Caulk** that is formulated to meet the quality standards of the professional painting contractor. This caulk provides a reliable seal for seams around doors, drywall and window trim and applies fast and easily, providing durability and paintability. This advanced technology caulk combines advanced acrylic technology and to provide an economical airtight, weatherproof seal that remains flexible much longer than the average caulk.

USES:

DYNAMITE 3000 Siliconized Acrylic Latex Caulk is formulated for light and general duty repairs. It can be used on a variety of materials in many residential applications that do not require an "expansion joint" for architectural structural adjustments.

Can be used on:

- Concrete and Stucco
- Metal and Aluminum
- Glass and Ceramic
- Stone and Brick
- Wood and Baseboards

KEY FEATURE: Easy to use with excellent paintability, no "shiners".

ADVANTAGES:

- Maintains a quality finish on general residential applications where there is minimal joint movement. For difficult applications requiring more flexibility due to joint movement use **DYNAMITE 7000**.
- Formulated to be either painted or go unpainted when painted, will not cause "shiners" or bleedthrough telegraphing repairs.
- Patented plunger means: No afterflow.
- Resists dirt pickup
- Cleans up easily with soap & water.

SURFACE PREPARATION:

Apply to sound, clean, and dry surfaces. Remove old caulk. Joints deeper than 1/2" should be filled with a backer material then sealed with **DYNAMITE 3000**.

APPLICATION TEMPERATURE:

Apply at temperatures above 40 degrees Fahrenheit. **DO NOT APPLY BELOW THE WATERLINE.**

APPLICATION:

Trim nozzle to desired bead size and apply caulk with caulking gun. Wipe off excess material with damp cloth or sponge. Use soap and water to clean up hands and tools.

COVERAGE:

When applied as a 3/8" bead, **Dynamite 3000** will cover approximately 20 linear feet. Applying a 1/8" bead will yield over 40 linear feet.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Meets:	ASTM C 834
Color:	White
Odor:	Mild
Consistency:	Smooth Paste
Flash Point:	Not Applicable
Vehicle:	Acrylic and Latex Polymers
Solvent:	Water
Pigments:	Calcium Carbonate and Titanium Dioxide
Dry To Touch:	30 - 60 minutes
Cure Time:	5 - 7 Days
% Solids:	80% +/- 2%
Recommended Storage Temperature:	40 F to 100 F.
Recommended Application Range:	45 F to 100 F.
Service Temperature Range:	-10 F to 150 F.
Shelf Life:	12 months

Approx. Shipping Weights: (Note: All approx. weights include container.)

12 - 10.1 Fl. Oz. Tubes/Case:	15 lbs.
Cases Per Pallet:	140 Cases

CAUTION!: KEEP OUT OF REACH OF CHILDREN
Do Not Take Internally. Keep From Freezing.

INGREDIENTS:

Calcium Carbonate	CAS# 471-34-1
Latex Emulsions	CAS# Proprietary
Butyl Benzyl Phthalate	CAS# 85-68-7
Mineral Spirits	CAS# 8052-41-3
Ethylene Glycol	CAS# 107-21-1
Titanium Dioxide	CAS# 13463-67-7

See MSDS for more info

Sealant Technology, A Division of Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.sealanttechnology.com, www.gardner-gibson.com

