



Breathe Easy. Professional Results.

7676

NON-SHRINK WALL FIX™ Data Sheet

- Breathe healthier
- Virtual odorless
- Fast drying
- Mold/mildew resistant



SMART™ is a Zero VOC system, for wall prep and repair before painting.

SMART™ Non-Shrink Wall Fix Spackling may be used on interior surfaces such as drywall, plaster, wood, concrete and stucco to patch and repair small holes, cracks, crevices, dimples and damaged surfaces. Ideal for nail holes and damaged drywall. This ready-to-use, lightweight spackling will not shrink or crack, and requires no sanding. Easy to apply and paint. Provides a durable and long lasting patch.

APPLICATION: Surface must be clean, dry and free of foreign material. Some mixing may be needed before use. Apply with putty knife. For a smoother finish, dip putty knife into water and lightly smooth spackling. Only one coat should be needed for small repairs. When patching deeper than 1/4", apply two or more layers. Allow time to dry between applications. Latex paint may be used to cover after 30 minutes. Clean tools with water.

PRECAUTIONS: Do not use when temperatures are below 50°F. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not use on surfaces where movement is likely. Not recommended for use as a caulk or joint filler. Use a good quality paint after patch has dried. Do not use in drinking water or food systems.

COVERAGE RATE: Approx. 3 sq. ft per quart at 1/8" thickness.

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc., warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight Per Gallon	3.8 lbs. ± .2 lbs.
Solids by Weight, %	53% ± 1%
Combustible Solvents	None
Consistency	Putty knife or trowel
Dry Time (50% Relative Humidity, 70°F)	1 hour
Full Cure (50% Relative Humidity, 70°F)	24 hours
Application Temperatures	50°F and rising
Flammability	N/A (water-based)
Clean-up Tools	Soap and warm water

Approx. Shipping Weights: (Note: All approx. weights include container.)

(6) 1 quart containers/case	8 lbs.
(4) 1 gallon containers/case	20 lbs.

**CAUTION: EYE AND SKIN IRRITANT.
DO NOT INGEST.
KEEP OUT OF REACH OF CHILDREN.
USE ONLY WITH ADEQUATE VENTILATION.**

FIRST AID: SKIN CONTACT: Wash with soap and water. **EYE CONTACT:** Wash with plenty of clean, room temperature water. **INHALATION:** Remove to fresh air. **INGESTION:** Do not induce vomiting. Call physician immediately or poison control center. **Note:** Any dry sanding of cured spackling may result in airborne dust, causing irritation to eyes, nose, throat or upper respiratory system. Prolonged inhalation of excessive amounts of dust may have adverse pulmonary and respiratory effects. Wet sand whenever possible. Do not breathe dust. Use in a well ventilated area. Avoid skin and eye contact. Wear gloves and eye protection with side shields. Container should be tightly sealed after use.

VOC: 0 g/L (Less water and exempt)

Acrylic copolymer (Proprietary), Water (7732-18-5), Borosilicate Glass (65997-17-3)

CALIFORNIA PROPOSITION 65 REQUIRED WARNING

WARNING: This product contains chemicals known to the State of California to cause cancer and/or reproductive harm.

Warning! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead, <http://www.epa.gov/lead>.

© 2009 Gardner-Gibson, Inc.
Manufactured by: Gardner-Gibson, Inc.
Tampa, FL 33605



See MSDS for more info

high performance + no compromises



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com